



wirefield GTB65

72,000 hrs
L80/B10


WEATHERPROOF



Technical Specification

- GRP body, poured gasket with PMMA diffuser.
- Surface mount as standard and can be suspended.
- Stainless steel clips as standard.
- IP65.
- IK02.
- Integral emergency available.


Features

Wattage	22w to 65w
Lumens per Watt	Up to 149
CRI	80
L**B**	72,000 hours L80 B10
Driver	Fixed Output / Dali / 1-10V
Controls	PIR (IP54) / Microwave (IP65) / 
Colour Temperature	4000k
Temperature Rating	-20°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	A (mm)	C (mm)
GTB32/4K	22	3201	1277 x 116 x 99	800	700
GTB64/4K	44	6403	1277 x 116 x 99	800	700
GTB33/4K	23	3361	1577 x 116 x 99	1100	1000
GTB46/4K	33	4614	1577 x 116 x 99	1100	1000
GTB67/4K	45	6724	1577 x 116 x 99	1100	1000
GTB92/4K	65	9229	1577 x 116 x 99	1100	1000



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Sensor Options:

PIR (IP54)

Microwave (IP65)

Eye-Wi

LED Options

Additional Options:

CCT 3000K / 6500K

Accessories

Optional Accessories:

Vandal Resistant Stainless Steel Clips

Besa Kit

Wall Mounting Brackets

Wire Guard

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained Self Test with Eye-Wi Reporting

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

Luminaire is not suitable for full external mounting. Please review the GTB66 luminaire if required and speak to the Wirefield Sales Office for more information.

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS