


High efficiency energy saving compact fluorescent decorative bulkhead, incorporating a 2D or T5 lamp, ideally suited to both internal and external applications requiring an IP65 rating.

Designed and manufactured to comply with EN 60598 and are CE certified.



Lamp Options



2D: 2D Compact Fluorescent



T5C: Circular

Product Specification

- Certified ingress protection to IP65
- White body
- Quick release opal diffuser for speedy maintenance
- Unique push fit conduit entry from one side
- High efficiency energy saving 2D or T5 lamp included
- Suitable for wall or ceiling mounting
- UV stabilised polycarbonate body and opal diffuser for maximum durability
- Quality integral control gear for long service life
- All gaskets are manufactured from heat resistant silicone rubber to ensure the IP65 rating

Optional Features

(Add suffix to order code)

/FTB: Fused terminal block

Order Codes

Including Lamps

Ashwood IP65 330

Order Code	Watt	Ø	H	Lamp
ASHW16/330	16	330	126	2D
ASHW22/330	22	330	126	T5C
ASHW28/330	28	330	126	2D
ASHW38/330	38	330	126	2D

Example order code:

ASHW28/330/E3 – A 28 watt 2D IP65 fitting with an opal diffuser, white body and fitted with integral 3 hour emergency pack. Supplied complete with lamp.

Gear options

/HF: High Frequency
/F: 10% Standby Dimming
/D: DSI Digital Dimming

/E3: 3hr Emergency
/E3T: Self Test Emergency

Please check with sales team for compatibility

Applications:

- Schools and universities
- Sports and leisure facilities
- Wash rooms and changing rooms
- Hotels
- Foyers, receptions and entrance halls
- Access areas requiring a semi-decorative appearance
- Under canopy applications



Also available with Motion and Daylight sensors - see page 156-157