



wirefield CALSHOT

50,000 hrs
L80/B50

FLOODLIGHT



Technical Specification

- Die cast aluminium housing in RAL 7004 and glass cover.
- Surface mount via stirrup.
- 120 degree beam angle.
- IP65.
- IK08.
- Emergency not available.

This product is not suitable for swimming pool or coastal environments, please speak to Wirefield sales for further information


Features

Wattage	30w to 240w
Lumens per Watt	Up to 105
CRI	80
L**B**	50,000 hours L80 B50
Driver	Fixed Output
Controls	PEC
Colour Temperature	4500k
Temperature Rating	-20°C to +35°C

LIGHTING INNOVATION FOR EXTERIOR APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
CFLED30	30	2747	320 x 240 x 80	2.3
CFLED50	50	4636	395 x 325 x 105	4.2
CFLED80	80	7744	370 x 250 x 95	4.5
CFLED120	120	12230	460 x 335 x 115	8.2
CFLED200	200	20872	550 x 425 x 145	13.5
CFLED240	240	22928	550 x 425 x 145	13.5



Control Options

Driver Options:

Sensor Options:

Fixed Output

PEC

Emergency Options

Emergency Options:

Not available

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR EXTERIOR APPLICATIONS