

wirefield COTTESMORE

50,000 hrs
L80/B30

**SURFACE
MOUNTED**



/BL: Black body



Side cable entry



Technical Specification

- White polycarbonate body and diffuser.
- Surface mount.
- Available in black body.
- IP65.
- IK10.
- Integral emergency available.


Features

| | |
|--------------------|---|
| Wattage | 15w to 25w |
| Lumens per Watt | Up to 88 |
| CRI | 80 |
| L**B** | 50,000 hours L80 B30 |
| Driver | Fixed Output / Dali / Corridor Function |
| Controls | Microwave |
| Colour Temperature | 4000k |
| Temperature Rating | -20°C to +30°C (excluding emergency) |

LIGHTING INNOVATION FOR AMENITY APPLICATIONS

Product Specification

| Code | Watts | Delivered lumens | D (mm) | Ø (mm) | Weight (kg) |
|----------|-------|------------------|--------|--------|-------------|
| COT15/4K | 15 | 1347 | 100 | 300 | 0.9 |
| COT25/4K | 25 | 2102 | 135 | 400 | 1.6 |



Control Options

Driver Options:

Fixed Output

DALI Driver

Corridor Function

Sensor Options:

Microwave

Accessories

Optional Accessories:

Black Body

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR AMENITY APPLICATIONS