



wirefield DISC

36,000 hrs
L70/B50

RECESSED
SLIMLINE IP44
DOWNLIGHT



Technical Specification

- Aluminium housing with opal diffuser.
- Recessed mounting.
- IP44.
- IK04.


Features

Wattage	6w to 24w
Lumens per Watt	Up to 75
CRI	80
L**B**	36,000 hours L70 B50
Driver	Fixed Output / Switch Dim / Dali
Colour Temperature	4000k
Temperature Rating	0°C to +30°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	Ø x H (mm)	Cut Out (mm)	Weight (kg)
RDR1063K	6	427	120 x 12	110	0.28
RDR1093K	9	649	150 x 12	135	0.30
RDR1123K	12	901	170 x 12	160	0.32
RDR1153K	15	1071	190 x 12	180	0.46
RDR1183K	18	1324	225 x 12	210	0.54
RDR1243K	24	1714	240 x 12	225	0.60
RDR1064K	6	450	120 x 12	110	0.28
RDR1094K	9	676	150 x 12	135	0.30
RDR1124K	12	917	170 x 12	160	0.32
RDR1154K	15	1125	190 x 12	180	0.46
RDR1184K	18	1351	225 x 12	210	0.54
RDR1244K	24	1800	240 x 12	225	0.60



Control Options

Driver Options:

Fixed Output

DALI Driver

Switch Dim

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Maintained

Full photometry and LDT files available on request

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS