Order Codes (must include a Suffix from the Intelligent Options)

1 x 40

1 x 55

2 x 40

2 x 55

Watt

1 x 40

1 x 55

2 x 40

2 x 55

Watt

2 x 40

2 x 55

Watt

2 x 40

2 x 55

ECLE2PL40/FP01 - A 2 x 40 watt PL-L Eve Eclipse Lunar 600 x 600 luminaire with perforated basket which dims between 10% and 100% depending on presence and

daylight detected by integral PIR. Supplied without lamps

6.4

6.4

6.4

6.4

Kg

6.4

6.4

6.4

6.4

Kg

6.4

6.4

Ka

6.4

PL-L

Lamp

PL-L

Eclipse Lunar Perforated Basket

Eclipse Solar Aluminium Louvre

Eclipse Lunar Drop Basket 2





The Eye Eclipse is a popular and efficient alternative to louvred products and is available with either a plain perforated diffuser or aluminium louvre.

> This attractive luminaire creates a subtle lighting effect utilising an involute reflector system, which allows a combination of direct and indirect lighting and stylish design.







Eclipse Lunar Perforated Basket



Eclipse Solar Aluminium Louvre



Eclipse Lunar Drop Basket 2



Eclipse Solar 2

Applications:

- Offices
- Shops Corridors
- Commercial applications
- Reception areas

Product Specification

595

- · High frequency control gear
- Fitted with a fused terminal block

Designed and manufactured to comply with EN 60598 and is CE certified.

595

- Direct/Indirect luminaire for optimum visual comfort
- Available with perforated downlight panel or parabolic louvre insert
- Powder coated RAL9010

Installation

Exposed T

Metal Pan

Suspended

Speed Wiring

/TW3 - 3 way

/TW4 - 4 way

/TW6 - 6 way

Surface

Plasterboard

- The ECLE versions can be layed into 15mm and 24mm T-Bar ceilings only
- An ECA compliance calculator is available on our website to verify compliance of this or any other luminaire with the latest ECA standard

Intelligent Options

(Add suffix to order code)

Integral Sensor

0

/FP01: PIR with 10% on standby

/FSLV: Slave luminaire for use with /FP01 master luminaire

Remote Sensor

/DSLV: Slave luminaire for use with remote sensor SEN-M10 for presence detection and daylight linking

Optional Accessories

SEN-M10: Presence detection and daylight linking sensor for use with /DSLV. Cannot be used in conjuction with /FP01 or /FSLV

Optional Features

(Add suffix to order code)

PU/: Replace ECLE prefix with ECLA for pullup version that can be installed into T-Bar. plasterboard and concealed fix ceilings with the use of the SB4 suspension brackets

/LFIX: Supplied with Lumafix side arm

/840: Supplied with colour 840 lamps

Intelligent Options

1

Our technical team can help you to design a practical solution for your specific needs.

Please contact us so that we can assist you to consider the best options from our full range of lighting controls.

Lamp Options

Excluding Lamps

Order Code

ECLE1PL40

ECLE1PL55

ECLE2PL40

ECLE2PL55

Order Code

ECLE1PL40/AL

ECLE1PL55/AL

ECLE2PL40/AL

ECLE2PL55/AL

Order Code

Order Code

ECLE2PL40/DB

ECLE2PL55/DB

Eclipse Solar 2

ECLA2PL40/DB/AL

ECLA2PL55/DB/AL

Example order code:





Gear options /M3: 3hr Emergency /S3: Self Test Emergency

See Page 214-215 for details