



WBL60



WBL11

HORTO

36W-125W
TC-D/TC-T/GLS
SI/M/QP

1 YEAR*
WARRANTY

IP65
RATING

OP. TEMP
-20°C
to
+40°C

VOLTAGE
AC220 - 240V

- Heavy duty IP65 high efficiency amenity bollard in two sizes 1100mm and 500mm, incorporating either GLS, metal halide, sodium, mercury or compact fluorescent lamps.
- Louvre stack for controlled light distribution. UV stabilised impact resistant polycarbonate refractor.
- Extra strong base plate mounting (root mounting version available). Tamper proof corrosion resistant fixings.
- Durable heavy grade aluminium body finished in corrosion resistant black.
- Quality integral control gear for trouble free use.

Code	Description - Including Lamps	Watt
WBL1118PL	Bollard 1100mm, aluminium body - TC-D lamps	2x18
WBL1142PL	Bollard 1100mm, aluminium body - TC-T lamp	1x42
WBL1110GLS	Bollard 1100mm, aluminium body - GLS lamp	1x100
WBL1170S	Bollard 1100mm, aluminium body - SI lamp SON	1x70
WBL1118PL	Bollard 1100mm, aluminium body - TC-D lamps	2x18
WBL1180M	Bollard 1100mm, aluminium body - M lamp Mercury	1x80
WBL1112M	Bollard 1100mm, aluminium body - M lamp Mercury	1x125
WBL6018PL	Bollard 500mm, aluminium body - TC-D lamps	2x18
WBL6042PL	Bollard 500mm, aluminium body - TC-T lamp	1x42
WBL6010GLS	Bollard 500mm, aluminium body - GLS lamp	1x100
WBL6070S	Bollard 500mm, aluminium body - SI lamp SON	1x70
WBL6070QP	Bollard 500mm, aluminium body - QP lamp Metal Halide	1x70

* GLS version supplied without lamp

