

LED EMERGENCY LIGHTING

BARNACK BULKHEAD

- The Barnack emergency bulkhead is suitable for internal and external environments.
- Manufactured in a moulded polycarbonate base. IP65 Rated.
- Fitted with a Fresnel diffuser. Supplied with a universal legend kit.
- A 20mm cable entry provided in the base. Hinged gear tray.
- This is a dual fitting – Will be operated in either maintained or non-maintained operation.



Code	Description	Watt
BAR4W	Maintained/Non maintained, polycarbonate base & Fresnel diffuser - LED	4

Code	L	W	H
BAR4W	353	112	58

Optional Features (add suffix to order code)

/PC: Photo Cell **/TS:** Test Switch **/SRK:** Semi-recessed Kit



KETTON EXIT ROUTE SIGN

- The Ketton exit route sign is suitable for internal environments.
- All Exit signs are arrow down as standard, please specify other direction if required.
- Viewing distance 34 metres.
- Wall mounted.
- This is a dual fitting – Will be operated in either maintained or non-maintained operation.



Code	Description	Watt
KET4W	Robust sheet steel exit sign - LED	4

Optional Features (add suffix to order code)

/TS: Test Switch **/ST:** Self Test **/UP /LEFT /RIGHT**



Code	L	W	H
KET4W	375	195	60

OAKHAM EXIT ROUTE SIGN

- The Oakham exit route sign is a double sided emergency sign suitable for internal environments.
- All Exit signs are arrow down as standard, please specify other direction if required.
- Viewing distance 16 metres.
- Ceiling mounted.
- Maintained as standard.



Code	Description	Watt
OAK3W	Double sided blade style - LED	3

Code	L	W	H
OAK3W	310	95	65

Optional Features (add suffix to order code)

/RK: Recessing Kit **/SMB:** Surface Mounting Box **/EVD:** Extended Viewing Distance 32 metres **/UP /LEFT /RIGHT**

