



Code	L
LP128	1221
LP154	1221
LP135	1541
LP149	1541
LP180	1541
LP228	1221
LP254	1221
LP235	1521
LP249	1521
LP280	1521

LIPACK



28W-160W T5	1 YEAR* WARRANTY	IP20 RATING	OP. TEMP -20°C to +40°C	VOLTAGE AC220 - 240V	WIRELESS COMPATIBLE Eye-Wi
-----------------------	----------------------------	-----------------------	---	--------------------------------	--

- The LiPack fitting is suitable for general, industrial and commercial applications.
- 4ft or 5ft single and twins.
- High strength sheet metal resilient white body.
- High frequency control gear as standard.
- Polycarbonate lamp holders.
- Gland entry points at both ends, plus on back of body.
- Range of accessories available.



Code	Description - Including Lamps	Watt
LP128	High frequency 4ft single - T5 lamp	1x28
LP154	High frequency 4ft single - T5 lamp	1x54
LP135	High frequency 5ft single - T5 lamp	1x35
LP149	High frequency 5ft single - T5 lamp	1x49
LP180	High frequency 5ft single - T5 lamp	1x80
LP228	High frequency 4ft single - T5 lamps	2x28
LP254	High frequency 4ft single - T5 lamps	2x54
LP235	High frequency 5ft single - T5 lamps	2x35
LP249	High frequency 5ft single - T5 lamps	2x49
LP280	High frequency 5ft single - T5 lamps	2x80

Potential Return on Investment

Annual cost saving £4,028	Lifetime cost saving £28,200	Lifetime CO² reduction 13T/CO²e
--	---	--

Energy and maintenance savings are based on 18 hour a day, 7 day a week operation against fluorescent switchstart battens.

Additional savings will be available through the use of lighting controls.

LINEAR LIGHTING This fitting is available with a wide variety of dimmable control options including Eye-Wi. Contact the sales office for more information.

Wirefield Limited Unit 1, Matrix Park, Talbot Road, Segensworth, Fareham, Hampshire PO15 5AP
T: 0844 847 5100 F: 0844 847 5101 www.wirefield.co.uk sales@wirefield.co.uk

All dimensions shown are in millimetres

wirefield 43