

# EMERGENCY



## OAKHAM EXIT ROUTE SIGN

- Single sided emergency exit sign suitable for internal environments.
- All Exit signs are arrow down as standard, please specify other direction if required.
- Viewing distance 16 metres.
- Ceiling mounted.
- Dual operation - maintained or non-maintained.

Code	Watts	Delivered lumens	L (mm)	W (mm)	D (mm)	Weight (kg)
OAK3W	3	52	285	130	25	0.5

**Optional Features** (add suffix to order code)

/RK: Recessing Kit /SMB: Surface Mounting Box /EVD: Extended Viewing Distance 32 metres

/ST: Self Test /UP /LEFT /RIGHT Arrow direction



## GRETTON II TWIN SPOT

- Provides a long lasting solution suitable for internal environments.
- Non-maintained with 3hr emergency output.
- Independently adjustable heads.
- Multiple mounting options.

Code	Watts	Delivered lumens	L (mm)	W (mm)	D (mm)	Weight (kg)
CAR30/IP20	15	720	260	300	70	1.9
CAR30/IP65	15	720	285	280	75	1.9




### Luminaire Spacing (Centre to centre in metres) on emergency escape routes

Mounting height	Transverse distance to wall Back-Side-Front	Transverse to transverse spacing
2.5m	3.9m-4.9m-8.0m	10.0m
4m	4.8m-5.6m-10.0m	13.0m
6m	5.5m-7.0m-12.5m	15.0m
8m	5.6m-7.6m-13.3m	15.3m

## MORCOTT EMERGENCY DOWNLIGHT

- Suitable for corridors, open spaces and internal environments.
- High Output LED light source.
- Supplied with white and chrome bezels as standard.
- Non-maintained.
- 35mm cut-out.

Code	Watts	Delivered lumens	Ø (mm)	D (mm)	Weight (kg)
MOR3W	5	120	55	25	0.3



CAR30/IP20



CAR30/IP65



Designed & manufactured to comply with EN 60598 and are CE certified.