

A linear vandal resistant IP65 surface mounted luminaire ideal for internal and external applications, particularly in onerous environments prone to vandalism.

Designed and manufactured to comply with EN 60598 and are CE certified.

Lamp Options



T5: 16mm Fluorescent Tubes



Product Specification

- Certified ingress protection to IP65
- Heavy gauge seam welded body
- Flat prismatic diffuser as standard
- Stainless steel vandal resistant screws
- High frequency control gear
- Colour 840 T5 lamps

Order Codes

Including Lamps

T5 Tube

Order Code	Watt	L	Lamp
PUR14/HF/840	1 x 14	750	T5
PUR28/HF/840	1 x 28	1352	T5
PUR35/HF/840	1 x 35	1652	T5
PUR49/HF/840	1 x 49	1652	T5
PUR54/HF/840	1 x 54	1352	T5
PUR214/HF/840	2 x 14	750	T5
PUR228/HF/840	2 x 28	1352	T5
PUR235/HF/840	2 x 35	1652	T5
PUR249/HF/840	2 x 49	1652	T5
PUR54/HF/840	2 x 54	1652	T5

Example order code:

PUR235/HF/840 – A Purlieus 2 X 35 watt high frequency col 840 IP65 luminaire. Supplied complete with lamps.

Gear options

/S: Retractive Switch Dimming

/D: DSI Digital Dimming

/E3: 3hr Emergency

/E3T: Self Test Emergency



Applications:

- Police Cells
- Police Stations
- Prisons
- Subways
- Walkways