



wirefield PLED

40,000 hrs
L70/B50

**SURFACE
MOUNTED**



Technical Specification

- Sheet steel body and opal PMMA diffuser.
- Surface mount.
- IP44.
- IK02.
- Integral microwave option available.
- Integral emergency available.


Features

Wattage	12w to 40w
Lumens per Watt	Up to 104
CRI	80
L**B**	40,000 hours L70 B50
Driver	Fixed Output / Dali / Corridor Function
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-15°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR AMENITY APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	D (mm)	Ø (mm)
PLED124K	12	1080	90	280
PLED184K	18	1700	105	360
PLED224K	22	2200	115	410
PLED324K	32	3200	115	410
PLED404K	40	4164	140	500



Control Options

Driver Options:

Fixed Output

DALI Driver

Corridor Function

Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained DALI Self Test

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR AMENITY APPLICATIONS