

# PRO65 T5



14W-98W  
T5

1 YEAR\*  
WARRANTY

IP65

IK08

OP. TEMP  
-0°C  
to  
+30°C

VOLTAGE  
AC220 - 240V



Code: SSCLIP/GRP

STAINLESS STEEL CLIPS



Code: SSCLIP/VR/GRP

STAINLESS STEEL VANDAL  
RESISTANT CLIPS




Code: GRP/HANGER

STAINLESS STEEL HANGER

Lamps not included

- Luminaire housing made of corrosion resistant glass fibre reinforced polyester with polycarbonate diffuser and one part plastic clips supplied as standard.
- Optional stainless steel clips (2ft x6, 4ft x8, 5ft x10, 6ft x12).
- Cable entries with grommets at both ends, and conduit entries on rear of housing.
- White powder coated metal hinged gear tray supports for 'hands free installation'.
- Available with **EyeWi** wireless controls.



A = Fixing centres  
C = Hanger positions



Code	Watts	L (mm)	W (mm)	D (mm)	A (mm)	C (mm)	Weight (kg)
GRP114*	1x14	669	90	95	460	366	1.8
GRP128	1x28	1277	90	95	800	700	2.8
GRP154	1x54	1277	90	95	800	700	2.8
GRP135	1x35	1577	90	95	1100	1000	3.8
GRP149	1x49	1577	90	95	1100	1000	3.8
GRP180	1x80	1577	90	95	1100	1000	3.8
GRP214	2x14	669	116	99	460	360	2.4
GRP228	2x28	1277	116	99	800	700	4.2
GRP254	2x54	1277	116	99	800	700	4.2
GRP235	2x35	1577	116	99	1100	1000	5.8
GRP249	2x49	1577	116	99	1100	1000	5.8

\* available with integral emergency but only in twin body

**Optional Features** (add suffix to order code)

/M3: 3hr integral emergency

Designed & manufactured to comply with EN 60598 and are CE certified.

Luminaire is not designed to be mounted in full external conditions- please speak to the Wirefield sales office for further information.

# PRO65 T8

18W-140W  
T8



1 YEAR\*  
WARRANTY



IP65



IK08



OP. TEMP  
-20°C\*  
to  
+30°C

VOLTAGE  
AC220 - 240V



Lamps not included



Code: SSCLIP/GRP

STAINLESS STEEL CLIPS




Code: SSCLIP/VR/GRP

STAINLESS STEEL VANDAL  
RESISTANT CLIPS



Code: GRP/HANGER

STAINLESS STEEL HANGER



A = Fixing centres  
C = Hanger positions



- Luminaire housing made of corrosion resistant glass fibre reinforced polyester with polycarbonate diffuser and one part plastic clips supplied as standard.
- Optional stainless steel clips (2ft x6, 4ft x8, 5ft x10, 6ft x12).
- Cable entries with grommets at both ends, and conduit entries on rear of housing.
- White powder coated metal hinged gear tray supports for 'hands free installation'.

Code	Watts	L (mm)	W (mm)	D (mm)	A (mm)	C(mm)	Weight (kg)
GRP118/HF**	1x18	669	90	95	460	360	1.8
GRP136/HF	1x36	1277	90	95	800	700	2.80
GRP158/HF	1x58	1577	90	95	1100	1000	3.80
GRP170/HF	1x70	1841	90	95	1164	1265	4.1
GRP218/HF	2x18	669	116	95	460	360	2.4
GRP236/HF	2x36	1277	116	99	800	700	4.2
GRP258/HF	2x58	1577	116	99	1100	1000	5.8
GRP270/HF	2x70	1841	116	99	1164	1264	6.4

\* Integral emergency version only suitable to 0°C

\*\* only available with remote emergency option /R3

**Optional Features** (add suffix to order code)

/M3\*: 3hr integral emergency

/CS-30: Cold store version (not available with integral emergency - please speak to the sales office for further information).

Designed & manufactured to comply with EN 60598 and are CE certified.

Luminaire is not designed to be mounted in full external conditions- please speak to the Wirefield sales office for further information.

T: 0844 847 5100 F: 0844 847 5101