




wirefield PROLED 100 HES

100,000 hrs
L80/B50

SURFACE MODULAR



Technical Specification

- Steel body with double parabolic aluminium louvred LED modules.
- Surface mount only.
- Available with connection accessory for continuous run.
- IP40.
- IK05.
- Integral emergency available.
- UGR <19.
- RAL colour options.


Features

Wattage	14w to 39w
Lumens per Watt	Up to 130
CRI	80+
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	Microwave Sensor / Bluetooth / Integral Daylight Sensor / CF / Smart Sensor
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
HES1144KA	14	1774	4000	595 x 175 x 40	2.0
HES1204KB	20	2541	4000	1215 x 175 x 40	4.0
HES1394KC	39	4878	4000	1555 x 175 x 45	4.7
HES2294KG	29	3658	4000	595 x 595 x 40	5.2
HES3394KG	39	4878	4000	595 x 595 x 40	5.3



Control Options

Driver Options:

Fixed Output

DALI

Switch Dim

Sensor Options:

Microwave Sensor

Bluetooth Control

Integral Daylight Sensor

Corridor Function

Smart Sensor

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained with DALI Interface

Integral Emergency with 'Escape Route' Optic

Integral Emergency with 'Open Area' Optic

Accessories

Optional Accessories:

RAL Colour Options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS