



wirefield

PROLED 100 HTG

100,000 hrs
L90/B10

STREET LIGHT



Technical Specification

- Die cast aluminium body and tempered glass cover.
- Post top mounting - Ø60mm.
- 140° x 140° beam angle.
- IP65.
- IK08.
- RAL colour options.



Features

Wattage	34w to 66w
Lumens per Watt	Up to 116
CRI	70+
L**B**	100,000 hours L90 B10
Driver	Fixed Output / DALI / CDIM
Controls	Photocell / 2 Level Auto-Dim
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	LM/W	CCT-K	L x W x H (mm)	Weight (kg)
HTG0344K	34	3960	116	4000	425 x 425 x 816	8.2
HTG0444K	44	4871	111	4000	425 x 425 x 816	8.2
HTG0514K	51	5940	116	4000	425 x 425 x 816	8.2
HTG0664K	66	7306	111	4000	425 x 425 x 816	8.2



Control Options

Driver Options:

Fixed Output

DALI Driver

CDIM

Sensor Options:

Photocell

2 Level Auto-Dim

LED Options

Additional Options:

CCT 3000K

Accessories

Optional Accessories:

RAL colour option - specify RAL colour.

Optics with asymmetric beam S1.

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS