



wirefield PROLED 100 HWY

100,000 hrs
L90/B10

STREET LIGHT



Technical Specification

- Die cast aluminium body.
- Tempered glass cover with quick release stainless steel clip.
- Side entry or post top mounting - Ø60mm.
- IP66.
- IK09.
- BS EN ISO 12944-2:2017 Category C4
- RAL colour options.

Features


Wattage	27w to 205w
Lumens per Watt	Up to 122
L**B**	100,000 hours L90 B10
Driver	Fixed Output / Dali / 1-10V
Controls	Photocell / 2 Level Auto-Dim
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS

wirefield PROLED 100 HWY

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
HWY304K	27	3018	522 x 216 x 137	3.2
HWY534K	44	5337	522 x 216 x 137	3.2
HWY894K	78	9054	629 x 268 x 148	4.6
HWY1184K	103	12072	629 x 268 x 148	4.6
HWY1484K	128	15090	752 x 310 x 178	7.2
HWY1594K	154	18108	752 x 310 x 178	7.2
HWY1774K	170	20328	863 x 359 x 199	12.0
HWY2364K	205	24144	863 x 359 x 199	12.0



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Sensor Options:

Photocell

2 Level Auto-Dim

LED Options

Additional Options:

CCT 3000K

CCT 5000K

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk

WIREFIELD 201901 V1.0