



wirefield PROLED 100 LVR

100,000 hrs
L80/B50

RECESSED UGR<19
MODULAR
LUMINAIRE



Technical Specification

- Steel powder coated body with polished aluminium louvres.
- Recessed mount into a 15mm/24mm ceiling grid or plasterboard ceiling.
- Ultra low glare luminaire.
- IP20.
- Integral emergency available.
- IK05.
- UGR <19.

Features

Wattage	27w to 37w
Lumens per Watt	Up to 122
CRI	80 +
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	Bluetooth
Colour Temperature	4000k
Temperature Rating	-0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	LM/W	CCT-K	L x W x D (mm)	Weight (kg)
LVR2334KA	33	3600	109	4000	595 x 595 x 52	3.6
LVR4274KA	27	3300	122	4000	595 x 595 x 52	3.6
LVR4374KA	37	4300	116	4000	595 x 595 x 52	3.6
LVR4274KB	27	3300	122	4000	1195 x 295 x 52	4.4
LVR4374KB	37	4300	116	4000	1195 x 295 x 52	4.4



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Sensor Options:

Bluetooth

LED Options

Additional Options:

CCT 3000K

CRI 90+

Emergency Options

Emergency Options:

Integral 3 hour emergency

Integral 3 hour emergency with auto test function

Accessories

Optional Accessories:

Matt Aluminium Louvres

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS