



wirefield

PROLED 100 RBC

100,000 hrs
L80/B50

RECESSED
FRAMELESS
DECORATIVE



Technical Specification

- Powder coated steel body.
- UV stable PMMA diffuser.
- 4 sizes - 300mm, 450mm, 600mm & 900mm diameter.
- IP20.
- Integral emergency options.


Features

Wattage	19w to 100w
Lumens per Watt	Up to 109
CRI	80+
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	MW / Bluetooth
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Cut Out (mm)	Weight (kg)
RBC1194KA	19	1798	4000K	300 x 125	315	2.50
RBC1274KA	27	2526	4000K	300 x 125	315	2.50
RBC1264KB	26	2839	4000K	450 x 125	465	4.80
RBC1374KB	37	3835	4000K	450 x 125	465	4.80
RBC1574KC	57	6199	4000K	600 x 135	615	7.50
RBC1824KC	82	8014	4000K	600 x 135	615	7.50
RBC1804KD	80	8332	4000K	900 x 150	915	10.50
RBC11004KD	100	10116	4000K	900 x 150	915	10.50



Control Options

Driver Options:

Fixed Output

DALI

Switch Dim

Sensor Options:

Microwave Sensor

Bluetooth Control

LED Options

Additional Options:

CCT 3000K

Tunable White 2700K to 6500K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained with DALI Interface

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS