



wirefield PROLED 100 RLR

100,000 hrs
L80/B50

**RECESSED
DECORATIVE**



Technical Specification

- Powder coated steel body.
- UV stable PMMA diffuser.
- 4 sizes - 320mm, 470mm, 620mm & 920mm diameter.
- Integral emergency options.
- RAL colour options.


Features

Wattage	19w to 100w
Lumens per Watt	Up to 109
CRI	80+
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	MW / Bluetooth
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Cut Out (mm)	Weight (kg)
RLR1194KA	19	1798	4000K	320 X180	300	4.00
RLR1274KA	27	2526	4000K	320 x 180	300	4.00
RLR1264KB	26	2839	4000K	470 x 180	450	6.80
RLR1374KB	37	3835	4000K	470 x 180	450	6.80
RLR1574KC	57	6199	4000K	620 x 190	600	10.00
RLR1824KC	82	8014	4000K	620 x 190	600	10.00
RLR1804KD	80	8332	4000K	920 x 210	900	14.00
RLR11004KD	100	10116	4000K	920 x 210	900	14.00



Control Options

Driver Options:

Fixed Output

DALI

Switch Dim

Sensor Options:

Microwave Sensor

Bluetooth Control

LED Options

Additional Options:

CCT 3000K

Tunable White 2700K to 6500K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained with DALI Interface

Accessories

Optional Accessories:

RAL Colour Options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS