



wirefield PROLED 100 TRL

100,000 hrs
L80/B50

SURFACE LINEAR
IP65 ANTI-VANDAL



Technical Specification

- Steel powder coated white body with opal diffuser fastened with vandal resistant screws in a steel frame.
- Surface mount as standard.
- IP65.
- IK10.
- Integral emergency available.
- RAL colour options.

Features

Wattage	10w to 54w
Lumens per Watt	Up to 141
CRI	80
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-20°C to +40°C (excluding emergency)

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
TRL1104KA*	10	1226	380 x 135 x 65	3.0
TRL1134KA*	13	1548	380 x 135 x 65	3.0
TRL1144KB	14	1685	660 x 135 x 65	3.5
TRL1194KB	19	2334	660 x 135 x 65	3.5
TRL1224KB	22	2899	660 x 135 x 65	3.5
TRL1194KC	19	2528	940 x 135 x 65	5.5
TRL1284KC	28	3502	940 x 135 x 65	5.5
TRL1324KC	33	4214	940 x 135 x 65	5.5
TRL1254KD	25	3113	1220 x 135 x 65	7.4
TRL1374KD	37	4668	1220 x 135 x 65	7.4
TRL1434KD	43	5619	1220 x 135 x 65	7.4
TRL1314KE	31	3891	1500 x 135 x 65	9.2
TRL1414KE	41	5295	1500 x 135 x 65	9.2
TRL1464KE	46	5805	1500 x 135 x 65	9.2
TRL1544KE	54	7023	1500 x 135 x 65	9.2

*EMERGENCY NOT AVAILABLE



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Accessories/Options

Optional Accessories:

Various RAL colours

Security Drill Bit for 2 Hole Fixing

Full photometry and LDT files available on request

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS