



# wirefield PROLED 100 TRR

**100,000 hrs**  
**L80/B50**

**RECESSED LINEAR**  
**IP65 ANTI-VANDAL**



## Technical Specification

- Steel powder coated white body with opal diffuser fastened with vandal resistant screws in a steel frame.
- Surface mount as standard.
- IP65.
- IK10.
- Integral emergency available.
- RAL colour options.

## Features

|                    |                                      |
|--------------------|--------------------------------------|
| Wattage            | 10w to 54w                           |
| Lumens per Watt    | Up to 141                            |
| CRI                | 80                                   |
| L**B**             | 100,000 hours L80 B50                |
| Driver             | Fixed Output / Dali / 1-10V          |
| Controls           | Microwave                            |
| Colour Temperature | 4000k                                |
| Temperature Rating | -20°C to +40°C (excluding emergency) |

*LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS*

## Product Specification

| Code       | Watts | Delivered lumens | L x W x D (mm)   | Weight (kg) |
|------------|-------|------------------|------------------|-------------|
| TRA1104KA* | 10    | 1296             | 380 x 135 x 135  | 3.0         |
| TRA1134KA* | 13    | 1636             | 380 x 135 x 135  | 3.0         |
| TRA1144KB  | 14    | 1780             | 660 x 135 x 135  | 3.5         |
| TRA1194KB  | 19    | 2466             | 660 x 135 x 135  | 3.5         |
| TRA1224KB  | 22    | 3078             | 660 x 135 x 135  | 3.5         |
| TRA1194KC  | 19    | 2670             | 940 x 135 x 135  | 5.5         |
| TRA1284KC  | 28    | 3699             | 940 x 135 x 135  | 5.5         |
| TRA1324KC  | 33    | 4451             | 940 x 135 x 135  | 5.5         |
| TRA1254KD  | 25    | 3288             | 1220 x 135 x 135 | 7.4         |
| TRA1374KD  | 37    | 4931             | 1220 x 135 x 135 | 7.4         |
| TRA1434KD  | 43    | 5936             | 1220 x 135 x 135 | 7.4         |
| TRA1314KE  | 31    | 4110             | 1500 x 135 x 135 | 9.2         |
| TRA1414KE  | 41    | 5623             | 1500 x 135 x 135 | 9.2         |
| TRA1464KE  | 46    | 6165             | 1500 x 135 x 135 | 9.2         |
| TRA1544KE  | 54    | 7419             | 1500 x 135 x 135 | 9.2         |

\*EMERGENCY NOT AVAILABLE



## Control Options

### Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

### Sensor Options:

Microwave

## LED Options

### Additional Options:

CCT 3000K

## Emergency Options

### Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

## Accessories/Options

### Optional Accessories:

Various RAL Colours

Security Drill Bit for 2 Hole Fixing

Full photometry and LDT files available on request

*LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS*