





wirefield

PROLED50 A11A

50,000 hrs
L80/B10

**TRACK
MOUNTED**



Technical Specification

- Powder coated die cast aluminium body.
- MacAdam 2 SDCM.
- Global 3-circuit track adaptor.
- RAL9006 – Silver, RAL9016 – White, RAL9005 – Black.
- Adjustable driver.
- Citizen 6th Generation LED COB.
- IP20.

Features

Wattage	17w to 42w
Lumens per Watt	Up to 126
CRI	90+ (Below BBL @ 3000K)
L*B**	50,000 hours L80 B10
Driver	Adjustable Fixed Output / DALI
Colour Temperature	4000k

LIGHTING INNOVATION FOR RETAIL APPLICATIONS



wirefield

PROLED50 A11A

Product Specification

COB38	CRI90+ 3000K Below BBL	CRI90+ 4000K	Reflector Options	Colour Options
17w (450ma)	2025lm	2150lm	15° 20° 30° 50°	Silver, White, Black
35W (900ma)	3600lm	3850lm	15° 20° 30° 50°	Silver, White, Black
42w (1050ma)	4000lm	4300lm	15° 20° 30° 50°	Silver, White, Black

LED Options

Additional Options:

CRI80+ 2700K, 3000K, 4000K, 5000K

CRI90+ 2700K Below BBL, 3500K Below BBL

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR RETAIL APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk