



wirefield

# PROLED50 CIP

**50,000 hrs**  
**L80/B50**

## IP65 CIRCULAR AMENITY BULKHEAD



### Technical Specification

- UV Stable Thermoplastic body and diffuser.
- IP65.
- IK08 (IK10 option).
- Integral emergency.
- Staircase and corridor function options.
- Decorative louvre option.
- White or Anthracite finish.

### Features

Wattage	9w or 14w
Lumens per Watt	Up to 119
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	Microwave / Master & Slave MW & Dim
Colour Temperature	4000k
Temperature Rating	-15°C to +35°C (excluding emergency)

*LIGHTING INNOVATION FOR AMENITY APPLICATIONS*

## Product Specification

### WHITE

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Weight (kg)
CIP1094KW	9	1102	4000	295 x 100	1.1
CIP1144KW	14	1539	4000	295 x 100	1.1

### ANTHRACITE


Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
CIP1094KG	9	1102	4000	295 x 100	1.1
CIP1144KG	14	1539	4000	295 x 100	1.1

### WHITE - LOUVRE

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Weight (kg)
CIP1094KWLOU	9	570	4000	295 x 100	1.1
CIP1144KWLOU	14	797	4000	295 x 100	1.1

### ANTHRACITE - LOUVRE

Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
CIP1094KGLOU	9	570	4000	295 x 100	1.1
CIP1144KGLOU	14	797	4000	295 x 100	1.1



## Control Options

### Driver Options:

Fixed Output  
DALI  
1-10v dimming

### Sensor Options:

MW On/Off  
MWRF - Corridor function master or slave dimming  
MWRF - Corridor function master or slave non-dimming

## LED Options

### Additional Options:

CCT 3000K

## Emergency Options

### Emergency Options:

3hr Integral Maintained  
3hr Integral Maintained Self Test  
3hr Integral Maintained with DALI Interface

## Accessories

### Optional Accessories:

IK10 diffuser

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

*LIGHTING INNOVATION FOR AMENITY APPLICATIONS*