



# wirefield PROLED50 EBR

**50,000 hrs**  
**L80/B50**

COMPACT ARCHITECTURAL  
LINEAR WALL-WASH



## Technical Specification

- Extruded aluminium body.
- UV resistant polycarbonate diffuser.
- IP66.
- IK09.
- 30 x 30° beam angle.


## Features

Wattage	16w to 60w
Lumens per Watt	Up to 127
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

*LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS*

### Product Specification

Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
EBR1164KA	16	1897	4000K	705 x 82 x 164	3.0
EBR1234KA	23	2370	4000K	705 x 82 x 164	3.0
EBR1304KA	30	3162	4000K	705 x 82 x 164	3.0
EBR1304KB	30	3794	4000K	1265 x 82 x 164	6.0
EBR1434KB	43	4740	4000K	1265 x 82 x 164	6.0
EBR1604KB	60	6324	4000K	1265 x 82 x 164	6.0



### Control Options

**Driver Options:**

Fixed output

DALI

### LED Options

**Additional Options:**

CCT 3000K

CCT 5000K

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

*LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS*