



wirefield PROLED50 ECP

50,000 hrs
L80/B50

**ECONOMIC SURFACE
OR SUSPENDED LINEAR**



Technical Specification

- Steel body with micro prismatic polycarbonate diffuser.
- White end caps with security screw fixing.
- Surface or suspended mounting.
- IP54.
- IK05.
- Integral emergency options.
- RAL colour options.


Features

Wattage	17w to 52w
Lumens per Watt	Up to 128
CRI	80
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	PIR / MW / MWRF dimming / MWRF non-dimming
Colour Temperature	4000k
Temperature Rating	-15°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
ECP1174KA	17	1862	615 x 97 x 72	1.5
ECP1224KA	22	2464	615 x 97 x 72	1.5
ECP1294KB	29	3724	1175 x 97 x 72	2.3
ECP1354KB	35	4350	1175 x 97 x 72	2.3
ECP1424KB	42	4928	1175 x 75 x 72	2.3
ECP1364KC	37	4704	1455 x 75 x 72	2.8
ECP1444KC	44	5495	1455 x 75 x 72	2.8
ECP1524KC	52	6225	1455 x 75 x 72	2.8



Control Options

Driver Options:

Fixed Output

DALI

1-10v

CF - Never off

CF - Off 1 minute

CF - Off 30 minutes

Sensor Options:

PIR

MW - On/Off

MWRF - Corridor function master or slave dimming

MWRF - Corridor function master or slave non-dimming

Accessories

Optional Accessories:

1.5m Adjustable Suspension Kit

2.0m Transparent 3 x 0.75mm Cable

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained with Self Test

3hr Integral with DALI Interface

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk