



wirefield

PROLED50 MAR

50,000 hrs
L80/B50

SURFACE BULKHEAD
IP65 ANTI VANDAL



Technical Specification

- Die-cast aluminium body, available as unpainted or dark grey on request.
- UV stabilised opal diffuser.
- Surface mount.
- IP65.
- IK10+.
- RAL 7043 grey when painted.


Features

Wattage	14w
Lumens per Watt	Up to 86
CRI	80
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-20°C to +40°C (excluding emergency)

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS

Product Specification

Code	Watts	Total Delivered lumens	D (mm)	Ø (mm)	Weight (kg)
MAR114K	14	1173	110	270	1.6
MAR114KLOU	14	902	110	270	1.6



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Accessories

Optional Accessories:

Half Louvre

Tamper Proof Screws

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS