



wirefield PROLED50 PKW

50,000 hrs
L90/B50

STREET LIGHT



Technical Specification

- Die Cast Aluminium Body.
- Round top Polycarbonate Canopy.
- Frosted Polycarbonate Diffuser.
- IP65.
- IK08.
- RAL colour options.


Features

Wattage	18w to 41w
Lumens per Watt	Up to 143
CRI	80+
L**B**	50,000 hours L90 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	Photocell
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	Ø x H (mm)	Weight (kg)
PKW1184K	18	2600	420 x 420	4.9
PKW1264K	26	3538	420 x 420	4.9
PKW1354K	35	4400	420 x 420	4.9
PKW1414K	41	4988	420 x 420	4.9



Control Options

Driver Options:

Fixed Output

DALI Driver

Switch Dim

Sensor Options:

Photocell

LED Options

Additional Options:

CCT 3000K

Accessories

Optional Accessories:

RAL colour options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR EXTERNAL APPLICATIONS