



wirefield

# PROLED50 PRD

**50,000 hrs**  
**L80/B50**

**RECESSED LED  
DOWNLIGHT**



## Technical Specification

- Recessed mounted with mounting brackets.
- Direct light distribution.
- Opal PMMA diffuser.
- White RAL9016 aluminium bezel.
- IP44.
- IK04.

## Features

Wattage	6w to 24w
Lumens per Watt	Up to 96
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Colour Temperature	3000k or 4000k
Temperature Rating	0°C to +35°C

*LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS*

## Product Specification

Code	Watts	Delivered lumens	CCT	CRI	Ø x H (mm)	Cut Out (mm)	Weight (kg)
PRD1063K	6	412	3000	80+	120 x 11	105	0.12
PRD1093K	9	778	3000	80+	145 x 11	130	0.18
PRD1123K	12	992	3000	80+	170 x 11	155	0.24
PRD1153K	15	1314	3000	80+	190 x 11	175	0.30
PRD1183K	18	1537	3000	80+	220 x 11	205	0.37
PRD1243K	24	2097	3000	80+	295 x 11	280	0.63
PRD1064K	6	465	4000	80+	120 x 11	105	0.12
PRD1094K	9	812	4000	80+	145 x 11	130	0.18
PRD1124K	12	1036	4000	80+	170 x 11	155	0.24
PRD1154K	15	1420	4000	80+	190 x 11	175	0.30
PRD1184K	18	1685	4000	80+	220 x 11	205	0.37
PRD1244K	24	2236	4000	80+	295 x 11	280	0.63



## Control Options

### Driver Options:

Fixed Output

DALI Driver

Switch Dim

## Emergency Options

### Emergency Options:

Remote 3hr maintained

Remote 3hr maintained, Tridonic brand

Full photometry and LDT files available on request

*LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS*