



wirefield PROLED50 RDB

50,000 hrs
L80/B50

ARCHITECTURAL
SMALL FORM
AMENITY



Technical Specification

- Die cast aluminium body.
- Impact resistant, UV stable opal polycarbonate diffuser.
- IP54.
- IK08.
- RAL colour options.


Features

Wattage	10w (7w Louvred version)
Lumens per Watt	Up to 83
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Weight (kg)
RDB1104K	10	835	4000K	270 x 80	1.4
RDB1074KLOU	7	451	4000K	270 x 85	1.6



Control Options

Driver Options:

Fixed Output
DALI Driver


Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K



Accessories

Optional Accessories:

RAL colour options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS