



wirefield

# PROLED50 RLED

**50,000 hrs**  
**L80/B10**

**SURFACE  
MOUNTED**



## Technical Specification

- Polycarbonate body and diffuser.
- Surface mount.
- Available with chrome or brass ring.
- IP20.
- IK05.
- Integral emergency available.


## Features

Wattage	15w to 29w
Lumens per Watt	Up to 110
CRI	80
L**B**	50,000 hours L80 B10
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	PIR / Microwave / 
Colour Temperature	4000k
Temperature Rating	-20°C to +30°C (excluding emergency)

*LIGHTING INNOVATION FOR AMENITY APPLICATIONS*

### Product Specification

Code	Watts	Delivered lumens	D (mm)	Ø (mm)
RLED15	15	1660	117	430
RLED23	23	2470	117	430
RLED29	29	3190	117	430



### Control Options

**Driver Options:**

Fixed Output

DALI Driver

1-10v

Corridor Function

**Sensor Options:**

PIR

Microwave

Eye-Wi

### LED Options

**Additional Options:**

CCT 3000K / 6000K

### Emergency Options

**Emergency Options:**

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained Self Test with Eye-Wi Reporting

### Accessories

**Optional Accessories:**

Chrome Ring

Brass Ring

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

*LIGHTING INNOVATION FOR AMENITY APPLICATIONS*