



wirefield

PROLED50 RTA

50,000 hrs
L80/B50

ARCHITECTURAL
COMPACT FORM
AMENITY



Technical Specification

- Die cast aluminium body.
- Impact resistant, UV stable opal polycarbonate diffuser.
- IP65.
- IK08.
- RAL colour options.



Features

Wattage	14w (11w Louvered version)
Lumens per Watt	Up to 86
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Weight (kg)
RTA1144K	14	1173	4000K	265 x 90	1.7
RTA1114KLOU	11	677	4000K	265 x 100	2.0



Control Options

Driver Options:

- Fixed Output
- DALI Driver

Sensor Options:

- Microwave

LED Options

Additional Options:

- CCT 3000K

Accessories

Optional Accessories:

- RAL colour options
- Security screws

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS