



wirefield PROLED50 RTB

50,000 hrs
L80/B50

ARCHITECTURAL
LARGE FORM
AMENITY



Technical Specification

- Die cast aluminium body.
- Impact resistant, UV stable opal polycarbonate diffuser.
- IP65.
- IK08.
- Integral emergency options.
- RAL colour options.


Features

Wattage	14w or 20w (10w or 14w Louvered version)
Lumens per Watt	Up to 89
CRI	80+
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-25°C to +40°C

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x D (mm)	Weight (kg)
RTB1144K	14	1252	4000K	360 x 130	2.5
RTB1214K	21	1759	4000K	360 x 130	2.5
RTB1104KLOU	10	642	4000K	360 x 145	2.6
RTB1144KLOU	14	902	4000K	360 x 145	2.6



Control Options

Driver Options:

Fixed Output
DALI Driver
Switch Dim


Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K



Emergency Options

Emergency Options:

3hr Integral Maintained
3hr Integral Maintained Self Test
3hr Integral Maintained with DALI Interface

Accessories

Optional Accessories:

RAL colour options
Security screws

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS