



wirefield

PROLED 75 CLD

75,000 hrs
L80/B50

SURFACE OR
SUSPENDED
DECORATIVE



Technical Specification

- Powder coated steel body and gear tray.
- Opal acrylic diffuser.
- Quick lock installation system.
- IP40.
- IK02.
- 4 sizes - 300mm, 450mm, 600mm & 900mm diameter.
- Integral emergency available.
- RAL colour options.


Features

Wattage	19w to 100w
Lumens per Watt	Up to 115
CRI	80
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	Bluetooth
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	Ø x D (mm)	Weight (kg)
CLD1194KA	19	1898	300 x 125	2.5
CLD1274KA	27	2574	300 x 125	2.5
CLD1254KB	25	2876	450 x 125	4.8
CLD1364KB	36	3914	450 x 125	4.8
CLD1554KC	55	6275	600 x 135	7.5
CLD1794KC	79	8540	600 x 135	7.5
CLD1794KD	79	8790	900 x 150	10.5
CLD11004KD	100	10847	900 x 150	10.5



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Microwave

Sensor Options:

Bluetooth

LED Options

Additional Options:

CCT 3000K

Tunable white

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Accessories

Optional Accessories:

Suspension Kit

RAL Colour Options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS