



wirefield PROLED 75 PBS

75,000 hrs
L80/B50

SURFACE MODULAR



Technical Specification

- Steel body, matt aluminium louvre and opal diffuser with asymmetric optic.
- Surface mounted.
- Available in 595 x 185 and 1195 x 185mm lengths.
- IP20.
- IK02.
- Emergency available.

Features

Wattage	15w to 42w
Lumens per Watt	Up to 108
CRI	80
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	None Integral
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
PBS1153KA	15	1413	595 x 185 x 60	2.0
PBS1213KA	21	2019	595 x 185 x 60	2.0
PBS1303KD	30	2982	1195 x 185 x 60	3.8
PBS1413KD	41	4262	1195 x 185 x 60	3.8
PBS1154KA	15	1480	595 x 185 x 60	2.0
PBS1214KA	21	2115	595 x 185 x 60	2.0
PBS1304KD	30	3124	1195 x 185 x 60	3.8
PBS1414KD	41	4465	1195 x 185 x 60	3.8



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS