



wirefield PROLED75 RDP

75,000 hrs
L80/B50

RECESSED
DOWNLIGHT
IP65



Technical Specification

- White powder coated aluminium body with silicone gasket.
- Faceted aluminium reflector and glass cover.
- IP65.
- IK05.
- 205mm cut-out.
- Emergency option.


Features

Wattage	20w & 42w
Lumens per Watt	Up to 112
CRI	80
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V
Controls	Eye-Wi
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	Ø x H (mm)	Cut Out (mm)	Weight (kg)
RDP1203K	20	2183	225 x 125	205	1.2
RDP1293K	29	2982	225 x 125	205	1.2
RDP1423K	42	4294	225 x 125	205	1.2
RDP1204K	20	2251	225 x 125	205	1.2
RDP1294K	29	3074	225 x 125	205	1.2
RDP1424K	42	4426	225 x 125	205	1.2



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Sensor Options:



LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Emergency pack

3hr Emergency pack

Full photometry and LDT files available on request

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS