



wirefield PROLED 75 RLU

100,000 hrs
L80/B50

UGR < 19 RECESSED
LINEAR FOR SUSPENDED
CEILING



Technical Specification

- Powder coated steel body.
- UGR < 19 glare control.
- 595mm and 1195mm option.
- IP40
- IK02
- Emergency options.
- In-line connection option.

Features

Wattage	14w to 29w
Lumens per Watt	Up to 127
CRI	80+
L**B**	100,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Colour Temperature	4000k
Temperature Rating	0°C to +35°C (excluding emergency)

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
RLU1144KA	14	1774	4000K	595 x 95 x 40	1.30
RLU1294KB	29	3658	4000K	1195 x 95 x 40	2.50



Control Options

Driver Options:

Fixed Output

DALI

Switch Dim

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

3hr Integral Maintained with DALI Interface

Accessories

Optional Accessories:

3 Pole or 5 pole pre-wired Wieland connector - 0.5m

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR COMMERCIAL APPLICATIONS