



wirefield

# PROLED75 SAA

**75,000 hrs**  
**L80/B50**

**SURFACE OR  
SUSPENDED  
DOWNLIGHT**



## Technical Specification

- Aluminium housing.
- UGR < 16 40° faceted aluminium reflector.
- IP20.
- IK02.
- RAL colour options.


## Features

Wattage	14w to 28w
Lumens per Watt	Up to 113
CRI	80+
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Colour Temperature	4000k
Temperature Rating	0°C to +35°C

*LIGHTING INNOVATION FOR RETAIL APPLICATIONS*

## Product Specification

Code	Watts	Delivered lumens	CCT	CRI	Ø x H (mm)	Weight (kg)
SAA1143K	14	1549	3000	80+	168 x 172	1.0
SAA1213K	21	2150	3000	80+	168 x 172	1.0
SAA1283K	28	2900	3000	80+	168 x 172	1.0
SAA1144K	14	1597	4000	80+	168 x 172	1.0
SAA1214K	21	2216	4000	80+	168 x 172	1.0
SAA1284K	28	2990	4000	80+	168 x 172	1.0



## Control Options

### Driver Options:

- Fixed Output
- DALI Driver
- Switch Dim

## LED Options

### Additional Options:

- CCT 3000K

## Accessories

### Optional Accessories:

- RAL colour options
- Suspension kit

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

*LIGHTING INNOVATION FOR RETAIL APPLICATIONS*