



# wirefield PROLED75 SDA

**75,000 hrs**  
**L80/B50**

**SURFACE  
DOWNLIGHT**



## Technical Specification

- Aluminium housing.
- Opal deep-set diffuser.
- IP44.
- IK04.
- Integral emergency.
- RAL colour options.


## Features

Wattage	13w to 23w
Lumens per Watt	Up to 116
CRI	80+
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Colour Temperature	4000k
Temperature Rating	0°C to +35°C

**LIGHTING INNOVATION FOR RETAIL APPLICATIONS**

## Product Specification

Code	Watts	Delivered lumens	CCT	CRI	Ø x H (mm)	Weight (kg)
SDA1123K	12	1261	3000	80+	200 x 130	1.0
SDA1163K	16	1774	3000	80+	200 x 130	1.0
SDA1233K	23	2458	3000	80+	200 x 130	1.0
SDA1124K	12	1321	4000	80+	200 x 130	1.0
SDA1164K	16	1858	4000	80+	200 x 130	1.0
SDA1234K	23	2575	4000	80+	200 x 130	1.0



## Control Options

### Driver Options:

Fixed Output  
DALI Driver  
Switch Dim

## LED Options

### Additional Options:

CCT 3000K

## Emergency Options

### Emergency Options:

3hr Integral Maintained (excluding 23w version)

## Accessories

### Optional Accessories:

RAL colour options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

*LIGHTING INNOVATION FOR RETAIL APPLICATIONS*