



wirefield PROLED75 TRL HP

75,000 hrs
L80/B50

SURFACE LINEAR
IP65 ANTI-VANDAL



Technical Specification

- Steel powder coated white body with opal diffuser fastened with vandal resistant screws in a steel frame.
- Surface mount as standard.
- IP65.
- IK10.
- Integral emergency available.
- RAL colour options.

Features

Wattage	51w to 64w
Lumens per Watt	Up to 112
CRI	80+
L**B**	75,000 hours L80 B50
Driver	Fixed Output / Dali / 1-10V / Corridor Function
Controls	Microwave
Colour Temperature	4000k
Temperature Rating	-20°C to +40°C (excluding emergency)

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS

wirefield PROLED 75 TRL HP

Product Specification

Code	Watts	Delivered lumens	CCT	L x W x D (mm)	Weight (kg)
TRA1514KD	51	5690	4000	1220 x 135 x 135	7.4
TRA1644KE	64	7112	4000	1500 x 135 x 135	9.2



Control Options

Driver Options:

Fixed Output

DALI Driver

1-10v

Corridor Function

Sensor Options:

Microwave

LED Options

Additional Options:

CCT 3000K

Emergency Options

Emergency Options:

3hr Integral Maintained

3hr Integral Maintained Self Test

Accessories/Options

Optional Accessories:

Various RAL colours

Security Drill Bit for 2 Hole Fixing

Full photometry and LDT files available on request

LIGHTING INNOVATION FOR INDUSTRIAL APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk