

# RETAIL DOWNLIGHTS



## LDL LED

- High performance recessed luminaire offering versatile lighting options for walls and shelves plus many other applications such as offices, hotels, reception areas and public buildings.
- Luminaire tilts 90° and turns 355°.
- Installation cut-out Ø180mm.

| Code  | Description   | Watt | Code  | L   | W   | H   |
|-------|---------------|------|-------|-----|-----|-----|
| LDL39 | 4600 lm - LED | 39   | LDL39 | 194 | 180 | 122 |
| LDL49 | 6500 lm - LED | 49   | LDL49 | 194 | 180 | 122 |



## MLDL LED

- High performance recessed luminaire offering flexible lighting options for walls and shelves plus many other applications such as offices, hotels, reception areas and public buildings.
- Luminaire tilts 90° and turns 355°.
- Installation cut-out Ø150mm.

| Code   | Description   | Watt | Code   | L   | W   | H  |
|--------|---------------|------|--------|-----|-----|----|
| MLDL33 | 4000 lm - LED | 33   | MLDL33 | 164 | 153 | 86 |

## S LED

- High performance economic recessed downlight offering flexible lighting options. Its high profile reduces glare even in low ceiling rooms plus many other applications such as offices, hotels, reception areas and public buildings.
- Installation cut-out Ø160mm.

| Code | Description   | Watt | Code | Ø   | W | H   |
|------|---------------|------|------|-----|---|-----|
| S16  | 2300 lm - LED | 16   | S16  | 179 | - | 131 |
| S39  | 4700 lm - LED | 39   | S39  | 179 | - | 131 |



| Code   | Watt | Kelvin |      |      | Beam Angle |    |    |    |    |    |    |    | Finish |        |       |
|--------|------|--------|------|------|------------|----|----|----|----|----|----|----|--------|--------|-------|
|        |      | 3000   | 4000 | 5000 | 10         | 15 | 20 | 24 | 30 | 40 | 50 | 60 | White  | Silver | Black |
| S16    | 16   | ✓      | ✓    | ✓    | -          | -  | -  | -  | -  | -  | -  | -  | ✓      | ✓      | ✓     |
| MLDL33 | 33   | ✓      | ✓    | ✓    | -          | ✓  | ✓  | -  | ✓  | -  | ✓  | -  | ✓      | ✓      | ✓     |
| S39    | 39   | ✓      | ✓    | ✓    | -          | -  | -  | -  | -  | -  | -  | ✓  | ✓      | ✓      | ✓     |
| LDL39  | 39   | ✓      | ✓    | ✓    | ✓          | -  | -  | ✓  | ✓  | -  | ✓  | -  | ✓      | ✓      | ✓     |
| LDL49  | 49   | ✓      | ✓    | ✓    | -          | -  | ✓  | -  | -  | ✓  | -  | ✓  | ✓      | ✓      | ✓     |

**Optional Features** (add suffix to order code)

/K: Kelvin /BA: Beam angle /W: White finish /S: Silver finish /B: Black finish

Example order code: **MLDL33/3000/50°/W**

- Ultimate LED reliability, premium brand with high power output.
- Choice of beam angle.
- Powder painted die-cast aluminium.
- Passive cooling.
- CRI 80%.
- Life 50,000hrs L70.