

An ultra slim range of circular metal based luminaires in a range of sizes and different finishes complete with polycarbonate diffuser.

Designed and manufactured to comply with EN 60598 and are CE certified.

This range also has a new backlight option.



HORIZONTAL OR VERTICAL MOUNTING



Lamp Options



2D: 2D Compact Fluorescent



T5C: Circular

Product Specification:

- Certified ingress protection to IP20
- Metal base for extra rigidity powder coated white as standard
- Opal polycarbonate diffuser
- Supplied with high frequency control gear as standard

Order Codes

Including Lamps

Retondo 325 2D

Order Code	Watt	Ø	H	Lamp
TON16/325	28	425	95	2D
TON28/325	28	425	95	2D

Retondo 425 2D

Order Code	Watt	Ø	H	Lamp
TON28/425	28	425	95	2D
TON38/425	38	425	95	2D

Retondo 525 T5

Order Code	Watt	Ø	H	Lamp
TON40/525	40	525	105	T5C
TON55/525/T5C	55	525	105	T5C
TON55/525/2D	55	525	105	2D

Example order code:

TON28/425 – A 28 watt 2D luminaire, 425mm diameter with high frequency control gear. Supplied complete with lamp.

Gear options

- /E3: 3hr Emergency
- /E3T: Self Test Emergency



Applications:

- Staircases
- Corridors
- Reception
- Hotel Rooms

Also available with Motion and Daylight sensors - see page 156-157