


A range of installation columns and brackets are available - Please contact our sales team for further information.



- High efficiency floodlight with UV stabilised impact resistant polycarbonate body incorporating metal halide, high pressure sodium, or mercury discharge lamp with power ratings ranging from 150 to 400 watts.
- Supplied as standard with timed ignitor to prevent lamp cycling. Highly durable UV stabilized impact resistant polycarbonate body.
- High purity symmetric reflector for improved efficiency, with an asymmetric reflector option. Wired with high temperature silicone insulated cable for maximum heat resistance. Easy maintenance with quick release toughened front glass. Adjustable stirrup with aiming facility for precision mounting.



Code	Description - Including Lamps	Watt
WFL150S/POLY	Black body, toughened glass - S lamp SON	150
WFL250S/POLY	Black body, toughened glass - S lamp SON	250
WFL400S/POLY	Black body, toughened glass - S lamp SON	400
WFL150QP/POLY	Black body, toughened glass - QP lamp Metal Halide	150
WFL250Q/POLY	Black body, toughened glass - Q lamp Metal Halide	250
WFL400Q/POLY	Black body, toughened glass - Q lamp Metal Halide	400
WFL250M/POLY	Black body, toughened glass - M lamp Mercury	250
WFL400M/POLY	Black body, toughened glass - M lamp Mercury	400

Optional Features (add suffix to order code)
 /FTB: Fused terminal block
 /PEC: Dusk to dawn sensing photo-electric cell
 /WG: Wire guard for improved protection
 /AS: Asymmetric reflector (sodium and metal halide only)

Wirefield Limited Unit 1, Matrix Park, Talbot Road, Segensworth, Fareham, Hampshire PO15 5AP
 T: 0844 847 5100 F: 0844 847 5101 www.wirefield.co.uk sales@wirefield.co.uk