



SOFTLED PRO



4000K/5000K COOL WHITE	100 LM/W	33W LED	5 YEAR* WARRANTY	IP20 RATING	CRI >80	50,000* HOURS	OP. TEMP -20°C to +40°C	VOLTAGE AC220 - 240V	WIRELESS COMPATIBLE Eye·Wi
----------------------------------	--------------------	-------------------	----------------------------	-----------------------	-------------------	-------------------------	---	--------------------------------	--

- The SoftLED Pro LED panel has been developed using quality components to provide a high light output for the life of the fitting.
- Unlike many LED panels the SoftLED Pro LED panel is fully serviceable lengthening the life expectancy of the fitting considerably.
- Offered in 4k and 5k colour temperatures.
- Backlit not edge lit with constant light output.
- Rigid resilient white finish metal frame and opal diffusing panel.
- LM80 tested.



Code	Description	Watt
WLP30/4K	White steel frame, opal diffuser 3350lm - LED	33
WLP30/5K	White steel frame, opal diffuser 3350lm - LED	33

Optional Features (add suffix to order code)
 /M3: 3hr integral emergency
This fitting is available with a wide variety of dimmable control options including Eye·Wi. Contact the sales office for more information.

Potential Return on Investment

Annual cost saving	Lifetime cost saving	Lifetime CO² reduction	Extended warranty
£11,584	£81,088	30T/CO₂e	5 years

Energy and maintenance savings are based on 18 hour a day, 7 day a week operation against fluorescent modular fittings.

Additional savings will be available through the use of lighting controls.

All dimensions shown are in millimetres