

The Spot-LED is a flexible 3 hour, maintained and non-maintained emergency LED luminaire which delivers superb light output performance from a 3 watt single white LED.

# Gear and batteries fit through cut out






## **Applications:**

• All emergency lighting applications

## Ambient temperature guidance

LED

0°C - +35°C



# **Product Specification**

- Max case temp (Tc) 70°C
- IP Rating of luminaire IP30
- Lumen output 148 lumens
- Charge indicator: Green + Red bi-colour LED
- ENEC approved
- SmartCharge<sup>™</sup> technology
- Operated in emergency by 3 x NiMH battery cells
- Articulated enclosure for discrete installation through fixed ceilings
- 3 year warranty
- AutoTest technology provides the user with self contained automatic testing in compliance to IEC62034
- Reflector finish to RAL9016
- DALI Emergency options give further benefits to the user enabling the testing and monitoring of the emergency lighting system on site or via the Internet
- · Maintained and non-maintained versions

Spot-LED distance table for an open area

Mounting height (m)	0.5 <b>2</b> →O	lux  O <b>→</b> O	1 lu Ø <b>→</b> O	ıx O <b>+</b> O
2.00	3.08	6.89	2.75	6.30
2.50	3.57	8.16	3.09	7.31
3.00	3.98	9.27	3.33	8.14
3.50	4.32	10.26	3.62	8.83
4.00	4.60	11.13	3.73	9.41

(Data based upon minimum light intensity of 0.5 lux /1 lux and an average lumen output of 148lm).

Key Distance from wall to first LED luminaire (m). O→O Specified distance required from one LED luminaire to another (m).

# **Auto-Test Operation**

LED green 10 second blink: Normal standby mode: Mains connected, charging, battery and power LED satisfactory

LED green slow flash: Commissioning mode or Duration Test in progress

LED green fast flash: Functional Test in progress

LED off: Mains not connected

LED red slow flash: Battery or charging system faulty

LED red fast flash: Defective power LED

# **SPOT-LED**

ULTRA LONG LIFE LED EMERGENCY DOWNLIGHT

For maintenance free general, retail and commercial application

## **Order Codes** Including Lamps

## MAINTAINED

Order Code	Watt	Lamp
E3LRM/A	3	LED
NON-MAINTAINED		
Order Code	Watt	Lamp
	3	
E3LR/A	3	LED

Example order code:

E3LRM/A – A 3 watt Spot-LED with high output 3 hour maintained emergency downlight delivering 148 lumens.