



ZONE 2 BULKHEAD



| | | | | |
|-------------------|----------------------------|-----------------------|---|--------------------------------|
| 70W S/Q | 1 YEAR* WARRANTY | IP65 RATING | OP. TEMP -20°C to +30°C | VOLTAGE AC220 - 240V |
|-------------------|----------------------------|-----------------------|---|--------------------------------|

- High efficiency wall mounted Zone 2, Cat 3 cast aluminium luminaire incorporating either 70 watt metal halide or, 70 watt high pressure sodium discharge lamp.
- Choice of metal halide or high pressure sodium lamp included.
- Suitable for gas and dust areas with restricted access.
- Highly durable heavy die cast aluminium body and optic frame.
- Quality sub components used for a long service life.
- Easy installation with two M20 ISO cable entries and large terminal block. All gaskets are manufactured from heat resistant silicone rubber to ensure IP65-rating.

| Code | Description - Including Lamps | Watt |
|---------------|---------------------------------------|------|
| ZBH70S | Zone 2 bulkhead - S lamp SON | 70 |
| ZBH70Q | Zone 2 bulkhead - Q lamp Metal Halide | 70 |

Certification code: EEx nC II 3 GD
T3 (Tamb -20 to + 30)
Certificate number 03 ATEX TFDN/01
(Restricted breathing).

